

Palm Canyon

Palm Canyon brings elevated style to any space. Inspired by the mid-century modern architecture of Palm Springs and the striking topography of desert mountains and cool blue pools, these hand-sculpted, three-dimensional, ceramic tiles are a celebration of iconic Mid-Century motifs. The thoughtfully-designed collection offers a multitude of pattern possibilities, and allows for the creation of unique, personalized spaces. Semi-translucent glazes emphasize the hand-crafted textures and dimensionality of each tile, while our palette of quiet, semi-matte hues connects harmoniously with both minimalist and maximalist spaces.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2025 Lunada Bay Tile. All Rights Reserved

| RECOMMENDED USAGE | | | FLOOR APPLICATIONS | | |
|--|-----------------------------|--|--|-------------|-------------------------|
| Application | | Suitable | | Interior | Exterior |
| Interior Wall/Backsplash | | Yes | Shower | No | No |
| Fireplace/Cooktop Surround | | Yes * | Steam Shower | No | N/A |
| Shower Wall | | Yes | Light Residential | Yes ▲ | No |
| Steam Shower | | Yes ** | Residential | No | No |
| Exterior Wall | | Yes | | | |
| Pool, Spa or Water Feature (fully submerged) | | Yes ** | | | |
| PRODUCT SPECS | | | TESTING | | |
| Size (Dimension In Nominal Size) | Coverage (Pieces per SF) | Packaging (Per Box) | Standards Methods | | |
| 4 ¾ x 9 ½ Field | 3.212 | 16 Pieces/4.981 SF | Breaking Strength | ASTM C-648 | > 450 PSI |
| Arc (4 ¾ x 4 ¾") | 6.452 | 32 Pieces/4.96 SF | Water Absorption | ASTM C-373 | Vitreous ≥ 0.5% -≤ 3.0% |
| Facet (4 ¾ x 4 ¾") | 6.452 | 32 Pieces/4.96 SF | Chemical Resistance | ASTM C-650 | Unaffected |
| Linocut (4 ¾ x 9 ½") | 3.212 | 16 Pieces/4.981 SF | Freeze/Thaw | ASTM C-1026 | Unaffected |
| Orbit (4 ¾ x 4 ¾") | 6.452 | 32 Pieces/4.96 SF | Warpage | ASTM C-485 | ± 0.26% / ± 1.5mm |
| Quadrant (4 ¾ x 4 ¾") | 6.452 | 32 Pieces/4.96 SF | NOTES | | |
| Liner (¾ x 9 ½") | | 80 Pieces | | | |
| Shade Variation | Grout Joint Recommendation | | | | |
| V1 - V2 Slight Variation | 1/8" (3 mm) | | Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed). | | |
| | | | | | |
| | | MAINTENANCE | | | |
| | | A routine cleaning of Palm Canyon can be done with light duty, diluted close to neutral pH cleaner. | | | |

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. **NOT** recommended for placement inside a firebox.

** **Aged Bronze** is not recommended for installation in pools, spas, water features or steam showers due to the metallic glaze.

▲ **Linocut and 4 ¾ x 9 ½ Field ONLY.** All other patterns are **NOT** recommended for use on floors.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.