

Point Lobos

Named for the California coastline where land meets the Pacific, POINT LOBOS captures elemental beauty in glazed high fire stoneware. Crafted in Japan with traditional techniques, each tile features iron spots and organic glaze variations inspired by the wild character of the Northern California coast and the handmade aesthetic of mid-century studio pottery.



SCAN CODE FOR MORE
INFORMATION ON
THE POINT LOBOS
COLLECTION

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE			FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior	
Interior Wall/Backsplash	Yes		Shower	Yes	Yes
Fireplace/Cooktop Surround	Yes *		Steam Shower	Yes	Yes
Shower Wall	Yes		Light Residential	Yes	Yes
Steam Shower	Yes		Residential	Yes	Yes
Exterior Wall	Yes		<i>Point Lobos series tiles meet slip resistance standards with a DCOF value ≥ 0.42 (ANSI A1371-2018) for commercial applications. See our website for full testing details and results.</i>		
Pool, Spa or Water Feature (fully submerged)	Yes				
PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage	Packaging (Per Box)	Standards Methods		
3" x 3" Mosaic	0.999 SF/Sheet	5 Sheets/4.994 SF	Breaking Strength	ASTM C-648	> 450 PSI
3 ½" x 9 ½"	0.233 SF/PC	20 Pieces/4.66 SF	Water Absorption	ASTM C-373	Vitreous $\geq 0.5\%$ - $\leq 3.0\%$
Liner ¾" x 9 ½"	0.787 LF/PC	80 Pieces/ 63 LF	Chemical Resistance	ASTM C-650	Unaffected
			Freeze/Thaw	ASTM C-1026	Unaffected
			Warpage	ASTM C-485	$\pm 0.26\%$ / $\pm 1.5\text{mm}$
Shade Variation	Grout Joint Recommendation		NOTES		
V3 to V4 Substantial Variation	1/8" (3 mm)		<p>Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).</p>		
			MAINTENANCE		
			<p>A routine cleaning of Point Lobos tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.</p>		

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. NOT recommended for

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.