Shinju Mirai

Tent (3 ½ x 9 ½")

Zen Garden (3 ½ x 9 ½")

Elon Hex Smooth (3 ½ x 9 ½")

Pianola (3 ½ x 9 ½")

From natural ocean treasures to meditative and mesmerizing environments — the Shinju series expands with Shinju Mirai, a larger format ceramic with sophisticated textures. Each design influences the sense of scale, transforms light, and creates resonance. Mix textures for a modern effect or use singly for a refined mood.





Unaffected

Unaffected

± 0.26% /± 1.5mm

Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2024 Lunada Bay Tile. All Rights Reserved

FLOOR APPLICATIONS

| Application | | | Suitable | | | Interior | | Exterior | | |
|--|-------------------------------------|----------------------------|----------|--|-------------------|----------|------------|----------|------------------------------|--|
| Interior Wall/Backsplash | | | Yes | Shower No No | | | No | | | |
| Fireplace/Cooktop Surround | | | Yes * | Steam Shower No N/A | | | | | | |
| Shower Wall | | | Yes | Light Residential Yes No | | | No | | | |
| Steam Shower | | | Yes ** | Residential | | No | | No | | |
| Exterior Wall | | | Yes ** | DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. | | | | | | |
| Pool, Spa or Water Feature (fully submerged) | | | | Yes ** | A 137.1-2018 | | | | | |
| PRODUCT SPECS | | | | TESTING | | | | | | |
| | Size (Dimension In Nominal Size) | Coverage (SF Per Piece) | | Packaging (Per Box) | Standards Methods | | | | | |
| | Paper (3 ½ x 9 ½") | 0.23 | 2 | 20 Pieces/4.66 SF | Breaking Strength | A | ASTM C-648 | | > 450 PSI | |
| | Serene (3 ½ x 9 ½") | 0.23 | 2 | 20 Pieces/4.66 SF | Water Absorption | A | ASTM C-373 | Viti | reous ≥ 0.5% - ≤ 3.0% | |
| | | | | | | | | | | |

13 Pieces/3.029 SF

20 Pieces/4.66 SF

20 Pieces/4.66 SF

20 Pieces/3.42 SF

| Elon Hex Reef (3 ½ x 9 ½") | 0.171 20 Pieces/3.42 | | | | |
|----------------------------|----------------------------|--------|--|--|--|
| Shade Variation | Grout Joint Recommendation | | | | |
| V1 - V3 Moderate Variation | 1/8" | (3 mm) | | | |

0.23

0.23

0.23

0 171

RECOMMENDED USAGE

NOTES

ASTM C-650

ASTM C-1026

ASTM C-485

Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. Installation constitutes acceptance. We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of **Shinju Mirai** tile can be done with a light duty nonabrasive, close to neutral pH detergent cleaner. Products with low pH and low alkalinity used for cleaning can eventually dull the finishes of Cape Pearl, Olympia, and Pacific over time.

- * Acceptable for limited and sporatic exposure near open flame or heat source, including fireplace wall/cooktop surround. NOT recommended for placement inside a firebox.
- ** Metallic Glazes: Cape Pearl, Olympia, and Pacific are not recommended for installations in pools, spas, water features, steam showers, or exterior walls directly exposed to the elements. All other colors are acceptable.
- ▲ Paper and Tent are dimensional tiles and thus **NOT** recommended for use on floors. All other sizes are acceptable.

FLOOR APPLICATION DEFINITIONS:

Chemical Resistance

Freeze/Thaw

Warpage

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.