

Watercolors

The masters of watercolor created nuanced paintings rich with emotion. The Watercolors ceramic series by Lunada Bay Tile pays homage to these famous artists through a curated collection of delicate to vibrant hues. Like miniature works of art, each handcrafted tile exhibits an artisanal aesthetic for a variety of spaces.



Please visit LunadaBayTile.com for our complete product offerings, applications and installation instructions.

© 2021 Lunada Bay Tile. All Rights Reserved

RECOMMENDED USAGE		FLOOR APPLICATIONS		
Application	Suitable		Interior	Exterior
Interior Wall/Backsplash	Yes	Shower	No	No
Fireplace/Cooktop Surround	Yes *	Steam Shower	No	N/A
Shower Wall	Yes	Light Residential	Yes	No
Steam Shower	Yes	Residential	No	No
Exterior Wall	Yes	<i>DCOF Value of ≥ 0.42 is accepted value for use in commercial applications. A 137.1-2018</i>		
Pool, Spa or Water Feature (fully submerged)	No			

PRODUCT SPECS			TESTING		
Size (Dimension In Nominal Size)	Coverage (SF per Piece)	Packaging (Per Box)	Standards Methods		
Picket (3 ½ x 9 ½")	0.188 SF	20 Pieces/3.76 SF	Breaking Strength	ASTM C-648	> 450 PSI
Plume (3 x 9")	0.194 SF	20 Pieces/3.88 SF	Water Absorption	ASTM C-373	Vitreous $\geq 0.5\%$ - $\leq 3.0\%$
Post (3 ½ x 9 ½")	0.233 SF	20 Pieces/4.66 SF	Chemical Resistance	ASTM C-650	Unaffected
Liner (¾ x 9 ½")		80 Pieces	Freeze/Thaw	ASTM C-1026	Unaffected
			Warpage	ASTM C-485	$\pm 0.26\%$ / $\pm 1.5\text{mm}$

Shade Variation	Grout Joint Recommendation	NOTES
V1 - V3 Moderate Variation	1/8" (3 mm)	

Since variations are common in artistic ceramic tile, we recommend final selection be made from an actual tile mock-up. To achieve optimal results in shading, layout and design, tile should be randomly selected from multiple boxes during installation. We recommend a minimum of 10% overage on all orders. Please take care when grouting and protect surface from abrasion. **Installation constitutes acceptance.** We advise retaining control samples to aid in color matching if additional material is required (match not guaranteed).

MAINTENANCE

A routine cleaning of **Watercolors** tile can be done with a light duty non-abrasive, close to neutral pH detergent cleaner.

* Acceptable for limited and sporadic exposure near open flame or heat source, including fireplace wall/cooktop surround. **NOT** recommended for placement inside a firebox.

FLOOR APPLICATION DEFINITIONS:

Light Residential - Flooring areas subject to soft-soled footwear or normal footwear traffic without abrasive soil/dirt, such as bathrooms and bedrooms without exterior access and minimal pivot points.

Residential - Flooring areas subject to soft-soled or normal footwear traffic that may contain amounts of abrasive soil/dirt, such as living rooms, dining rooms or other rooms with exterior access.